


**One Cell Lithium-ion/Polymer Battery Protection IC**

● **Features**

- Reduction in Board Size due to Miniature Package SOT-23-6.
- Ultra-Low Quiescent Current at 3μA (Vcc=3.9V).
- Auto recovery
- 0v charging
- Precision Overcharge Protection Voltage 4.375V ±25mV and 4.425V ±25mV
- Load Detection Function during Overcharge Mode.
- Two Detection Levels for Overcurrent Protection.
- Delay times are generated by internal circuits. No external capacitors required.

● **Pin Configuration**



● **General Description**

The SSC5918 battery protection IC is designed to protect lithium-ion/polymer battery from damage or degrading the lifetime due to overcharge, overdischarge, and/or overcurrent for one-cell lithium-ion/polymer battery powered systems, such as cellular phones

The ultra-small package and less required external components make it ideal to integrate the SSC5918 into the limited space of battery pack. The accurate ±25mV overcharging detection voltage ensures safe and full utilization charging. The very low standby current drains little current from the cell while in storage.

● **Applications**


- Protection IC for One-Cell Lithium-Ion/Lithium-Polymer Battery Pack
- built-in cell of mobile phone
- digital product cell
- camera cell
- portable power
- Reflow soldering internal actual temperature < 250 degrees, time in high temperature < 7 s.

Pin No.	Symbol	I/O	Description
1	OD	O	MOSFET gate connection pin for discharge control
2	CS	I	Input pin for current sense, charger detect
3	OC	O	MOSFET gate connection pin for charge control
4	TD	I	Test pin for reduce delay time
5	VCC	-	Power supply, through a resistor (R1)
6	GND	-	Ground pin


● **Product Name List**

Model	Package	Overcharge detection voltage [VOCP] (V)	Overcharge release voltage [VOCR] (V)	Overdischarge detection voltage [VODP] (V)	Overdischarge release voltage [VODR] (V)	Overcurrent detection voltage [VOI1] (mV)
	SOT23-6					
SSC5918H0a	SOT23-6	4.375±0.025	4.100±0.050	2.40±0.100	3.0±0.100	150±30
SSC5918H0b	SOT23-6	4.375±0.025	4.100±0.050	2.40±0.100	3.0±0.100	175±30
SSC5918G0a	SOT23-6	4.425±0.025	4.425±0.025	2.40±0.100	3.0±0.100	150±30


● **Package Information**



● Functional Block Diagram



● Typical Application Circuit



● **Absolute Maximum Ratings**(VSS=0V, Ta=25°C unless otherwise specified)


Item	Symbol	Rating	Unit
Input voltage between VDD and VSS *	V <sub>DD</sub>	VSS-0.3 to VSS+10	V
OC output pin voltage	V <sub>OC</sub>	VDD-26 to VDD+0.3	V
OD output pin voltage	V <sub>OD</sub>	VSS-0.3 to VDD+0.3	V
CS input pin voltage	V <sub>CS</sub>	VDD-26 to VDD+0.3	V
Operating Temperature Range	T <sub>OP</sub>	-40~+85	°C
Storage Temperature Range	T <sub>ST</sub>	-40~+125	°C

Note:SSC5918 contains a circuit that will protect it from static discharge; but please take special care that no excessive static electricity or voltage which exceeds the limit of the protection circuit will be applied to it.


● **Electrical Characteristics** (Ta=25°C unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Uni
Supply Current	V <sub>CC</sub> =3.9V	I <sub>CC</sub>		3.0	6.0	uA
Power-Down Current	V <sub>CC</sub> =2.0V	I <sub>PD</sub>			3.0	uA
Overcharge Protection Voltage	SSC5918H	V <sub>OCP</sub>	4.35	4.375	4.4	V
Overcharge Protection Voltage	SSC5918G	V <sub>OCP</sub>	4.4	4.425	4.45	V
Overcharge Release Voltage	SSC5918H	V <sub>OCR</sub>	4.05	4.10	4.15	V
Overcharge Release Voltage	SSC5918G	V <sub>OCR</sub>	4.4	4.425	4.45	V
Overdischarge Protection Voltage		V <sub>ODP</sub>	2.30	2.40	2.50	V
Overdischarge Release Voltage		V <sub>ODR</sub>	2.90	3.00	3.10	V
Overcurrent Protection Voltage		V <sub>OIP</sub> (V <sub>OI1</sub> )	120	150	180	mV
Short Current Protection Voltage	V <sub>CC</sub> =3.6V	V <sub>SIP</sub> (V <sub>OI2</sub> )	1.25	1.35	1.45	V
Overcharge Delay Time		T <sub>OC</sub>		80	200	ms
Overdischarge Delay Time	V <sub>CC</sub> =3.6V to 2.0V	T <sub>OD</sub>		40	100	ms
Overcurrent Delay Time (1)	V <sub>CC</sub> =3.6V	T <sub>OI1</sub>		10	20	ms
Overcurrent Delay Time (2)	V <sub>CC</sub> =3.6V	T <sub>OI2</sub>		5	100	us
Charger Detection Threshold Voltage		V <sub>CH</sub>	-1.2	-0.7	-0.2	V
OD Pin Output “H” Voltage		V <sub>DH</sub>	V <sub>CC</sub> -0.1	V <sub>CC</sub> -0.02		V
OD Pin Output “L” Voltage		V <sub>DL</sub>		0.1	0.5	V
OC Pin Output “H” Voltage		V <sub>CH</sub>	V <sub>CC</sub> -0.1	V <sub>CC</sub> -0.02		V
OC Pin Output “L” Voltage		V <sub>CL</sub>		0.1	0.5	V


● Timing Diagram



Overdischarge Condition     $\longrightarrow$     Charging by a Charger     $\longrightarrow$     Normal Condition



Over Current Condition → Normal Condition



**DISCLAIMER**

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE graphs PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE ) AND THEREFORE OUTSIDE THE WARRANTED RANGE.